

Semi-professional Embroidery Machines

Accessories Guide

Our wide variety of frames give you the versatility to embroider an extended range of products.























10-Needle Home Embroidery Machine with Built-in Camera

Maximum sewing area: 360 × 360 mm (14 × 14 in)



6-Needle Home Embroidery Machine with LED Positioning Marker

Maximum sewing area: 300 × 200 mm (12 × 8 in)



1-Needle Home Embroidery Machine with LED Positioning Marker

Maximum sewing area: 200 × 200 mm (8 × 8 in)

PR and VR Series Features ——— Extensive range of accessories

- LCD Screen
- Portability

- Automatic Needle Threading
- Automatic Frame Detector
- Wide variety of built-in designs and fonts

Easy hooping and centering with scratch-free

Flat brim cap frame PR1055X/PR1050X PR670E/PR655

130 × 60 mm (5 × 2.4 in)



PRCF5

VR

Sliding and ratchet frame fixing



Wider range of caps can be used

Embroider completed caps

Can go close to the brim, included brim cover

Cap Fran	ne		PRCF3
	PR1055X/PR1050X	PR670E/PR655	VR
130 × 60 mm (5 × 2.4 in)		\checkmark	





Set cap directly onto the machine



Stretch the cap over the frame



Embroider right up to the edge



Wider area for embroidery designs

Hooping thick materials with ease, avoid fabric shifting

Magnetic sash frame PR1055X/PR1050X PR670E

360 × 200 mm (14 × 8 in)

×*

*300 × 200 mm on 6 needle machine

VR

PRMS360



Easy hooping, only add magnet pieces







Easy to connect pattern, only slide the material



Included magnet lifter, easy to remove the magnetic pieces



Good for quilt sashing, too



Wide embroidery area

One hand operation for attaching and extending

Tubular frame tablePRTT1				
PR1055X/PR1050X	VR			
\checkmark	\checkmark	\checkmark		



One hand operation for attaching and extending





Minimum space with storing flat mechanism

Supporting heavy tubular materials



Embroider half the design with the garment hooped once

Rotate the frame when half the design is complete and embroider the rest of the design.

Apply embroidery to shoes and other pieces that were previously difficult to embroider

Clamp Fr	ame		PRCLP45B/PRCLP45LR/ VRCLP45B
	PR1055X/PR1050X	PR670E/PR655	VR
45 × 24 mm (1.7 × 1 in)	\checkmark	\checkmark	\checkmark
L: 45 × 24 mm (1.7 × 1 in)	\checkmark	\checkmark	
R: 45 × 24 mm (1.7 × 1 in)	\checkmark	\checkmark	







Set larger shoes



The VR is compatible with the straight type only




Embroider the collars of polo shirts

Easiest framing with strong holding power, yet no hoop burn

/	Clamp Fr	ame M		PRCLP100B/ VRCLP100B
		PR1055X/PR1050X	PR670E/PR655	VR
	100 × 100 mm (4 × 4 in)	\checkmark	\checkmark	\checkmark










Easiest framing - just click and snap



Double-sided frame surface to cover both woven and slippery material

Embroidery is easy even for those parts that offer little stretch such as pockets

Compact	Compact Frame/S Frame PRSFK1				
	PR1055X/PR1050X	PR670E/PR655	VR		
38 × 44 mm (1.5 × 1.7 in)	\checkmark	\checkmark	\checkmark		
41 × 70 mm (1.6 × 2.7 in)	\checkmark	\checkmark	\checkmark		
33 × 75 mm (1.3 × 2.9 in)	\checkmark	\checkmark	\checkmark		
50 × 50 mm (2 × 2 in)	\checkmark	\checkmark	\checkmark		



Embroidery is possible even in small spaces such as pockets, and support for automatic frame detection ensures both safety and peace-of-mind

Perfect for vertically long areas

 PRIO255X/PR1050X
 PR670E/PR655
 VR

 70 × 200 mm (2.7 × 8 in)
 V



Perfect for emboidery of vertically long areas such as pants and sleeves



Jacket and jumper sleeves can also be embroidered



Can also be used for infant rompers and children's shirts

Scan Fra	me		PRSCANFKIT1	N. T. C. T.
	PR1055X/PR1050X	PR670E/PR655	VR	
300 × 200 mm (12 × 8 in)	\checkmark			
			Included in PR1055X	



Set printed image on the frame



Secure with the magnets




Scan and import the image with My Design Center




The imported image can be edited and converted into embroidery data.





	Magnetic	Frame		PRMFA50
1		PR1055X/PR1050X	PR670E/PR655	VR
	50 × 50 mm (2 × 2 in)	\checkmark	\checkmark	\checkmark






Ideal for materials vulnerable to hoop burn, such as stretch fabric or knit.

Ideal for embroidering continuous designs such as those on curtains and skirts

Bo	order F	rame		PRPBF1/ VRBF180	1	·····
		PR1055X/PR1050X	PR670E/PR655	VR	Ĩ.	
300 ×	100 mm (12 × 4 in)	\checkmark	\checkmark			
180 ×	100 mm (7 × 4 in)			\checkmark	Jé	







Remove the frame in one step



The VR offers a 180 mm × 100 mm sewing range

Apply the frame over a specific area

Round Frame PRPRFK1/ VRRFK1			
	PR1055X/PR1050X	PR670E/PR655	VR
Φ100 mm (4 in) (dia)	\checkmark	\checkmark	\checkmark
Φ130 mm (5 in) (dia)	\checkmark	\checkmark	\checkmark
Φ160 mm (6 in) (dia)	\checkmark	\checkmark	\checkmark









Easily adjust designs that need to be properly aligned

1

Square frame to suit quilt designs



Square frame to make aligning quilt patterns and other embroidery positions easy





The square shape of the frame also makes it ideal for planning quilt designs

Excess cloth on larger pieces no longer gets in the way when embroidering

Flat Fram	ne		PRF300	
	PR1055X/PR1050X	PR670E/PR655	VR	4
300 × 200 mm (12 × 8 in)	\checkmark	\checkmark		L
	ANANANA A			



Cloth outside the frame is kept on top of the frame and out of the way



Even large pieces of cloth can hang over to the upper side of the arm



Other accessories

	PR1055X/PR1050X	PR670E	VR
Bobbin Winder	\checkmark	\checkmark	\checkmark
Wide Table	\checkmark	\checkmark	\checkmark
mbroidery Stand	\checkmark	\checkmark	\checkmark
Free Motion Kit			\checkmark
Bobbin Winder	Wide	Table	Embroidery Stand
PRBW	V1	PRWT1/VRWT1	PRNSTD2/VRPRNSTD
	5	5	È

Free Motion Kit





Main Specifications and Functions

	PR1055X	PR670E	VR
Number of needles	10	6	1
Speed adjustment	Individual Needle Speed adj	ustable from 400 to 1000 spm*(Frames); 400 to 600 s	pm (Caps/Cylinder/Clamps)
Maximum sewing area	360 × 360 mm (Wide cap frame: 360 × 60 mm)	300 × 200 mm (Cap frame: 130 × 60 mm)	200 × 200 mm (Cap frame: 130 × 60 mm)
$(W \times H)$	14 × 14 in (Wide cap frame: 14 × 2.4 in)	12 × 8 in (Cap frame: 5 × 2.4 in)	8 × 8 in (Cap frame: 5 × 2.4 in)
Maximum sewing area of included frame (W \times H)	360 × 200 mm 14 × 8 in	300 × 200 mm 12 × 8 in	200 × 200 mm 8 × 8 in
LCD	WVGA 1280 × 800 IPS 16,777,216 colours	WVGA 1280 × 800 IPS 16,777,216 colours	WVGA 800 × 480 TFT 260,000 colours
Input	2 USB ports (2.0)/1 PC connection (2.0)	2 USB ports (2.0)/1 PC connection (2.0)/1 SD card	1 USB ports/1 PC connection
Built in fonts	37	37	20
Built in design	944	640	305
Automatic needle threading	Yes	Yes	Yes
Needle position confirming	Camera/Live Camera	LED pointer	LED pointer
Manual color sequence	Yes	Yes	No
Sewing speed setting	Yes	Yes	No
Single colour sewing	Yes	Yes	Yes
Colour sort	Yes	Yes	Yes
Built-in tutorial videos	29	16	No
WLAN function	Yes	No	No

PR670E

PR Series Arm/Frame Compatibility

PR1055X

Models

е

50 × 50

Magnetic

В Е Arm А В С D Е А С D а b с d е Ε Sewing area Α B D Ε Α B C D С е а b d Frame Label sign (mm) 60 × 40 (No label) \checkmark \checkmark \checkmark \checkmark 100 × 100 (No label) \checkmark \checkmark V V ~ Tubular 180 × 130 (No label) \checkmark V 300 × 200 (No label) (No label) 360 × 200 \checkmark Flat (No label) \checkmark 300 × 200 1 B 200 × 200 Quilt \checkmark 1 Β 300 × 100 V Border \checkmark В 360 × 360 Jumbo \checkmark Β 70 × 200 Sleeve \checkmark V С Φ100 \checkmark \checkmark \checkmark С \checkmark Round Φ130 \checkmark \checkmark С Φ160 \checkmark \checkmark \checkmark D 45 × 24 \checkmark \checkmark \checkmark D L: 45 × 24 \checkmark \checkmark Clamp D R: 45 × 24 \checkmark \checkmark D M: 100 × 100 \checkmark \checkmark \checkmark а Tubular 200 × 200 \checkmark а \checkmark Quilt 200 x 200 b \checkmark Border 180 × 100 e 1 1 \checkmark 38 × 44 е \checkmark V 41 × 70 \checkmark S е 1 \checkmark 33 × 75 1 е 50 × 50 1 1 1